

TITLE: FIRE EXTINGUISHER 2.5 LB ABC		
DOCUMENT #: WI-FEXTG25	LABOR HOURS: 0.12	PRINT DATE: 2/26/21
REVISION: 1	PREPARED BY: V.Posa	DATE PREPARED: 01/27/2021
EFFECTIVE DATE: 2/10/2021	REVIEWED BY: M.McCLELLAND	DATE REVIEWED: 2/9/2021
FUNCTIONAL DEPARTMENT: Engineering	APPROVED BY: M.McCLELLAND	DATE APPROVED: 2/9/2021

- STANDARD WARNINGS:**
- READ WORK INSTRUCTIONS IN ENTIRETY BEFORE STARTING
 - CHECK THAT YOU ARE PROPERLY CLEAR OF GAS TANK AND WIRES BEFORE DRILLING
 - CONTACT ENGINEERING IF QUESTIONS ARISE OR DOCUMENT NEEDS TO BE UPDATED
 - FOLLOW ALL LISTED OEM SYSTEM FUNCTIONALITY CHECKS AFTER INSTALL.

PART IDENTIFICATION / BOM:

• 2 nd Item Number	Description	Qty-UM
• 020982	FIRE EXTINGUISHER 2.5# ABC	1-EA
• RM541013	WASH 1/4 ZN GR2	2-EA
• RM511458	BLT HWHD 1/4-20X3/4 ZN GR5	2-EA
• RM520312	NUT HEX NYLOC 1/4-20 ZN GR2	2-EA

TOOLS REQUIRED:

- 7/16 Socket -Deep Well 3/8 dr.
- 7/16 Combination Wrench (6pt.)
- Impact 3/8 dr. or Air Ratchet 3/8 dr.
- Drill w/ 17/64 (Screw Machine) Drill Bit

PROCESS:

- FEXTG25 will be assembled to the partition of the module at customer specified location.
- You would need to drill the holes for attaching fire extinguisher holder to the partition. Use customer specific templates for drilling holes on partition for mounting fire extinguisher.



OEM SYSTEM FUNCTIONALITY TESTING:

- N/A